



## WOYR2.E7458

## Switches, Appliance and Special Use - Component

LEVITON MFG CO INC  
201 N SERVICE RD  
MELVILLE, NY 11747-3138 USA

E7458

Investigated to ANSI/UL 1054

Cat. No.	Amps	Volts	Hz	Load	Endurance	Temp C	POL/THR	Per Pole/Circuit Code	SPCOA
<b>10041 /fb/ followed by 500 w/wo 501-999</b>									
	6	125	60	GP	6K	65	1/1	-/-	-
	3	250	60	GP	6K				
	3	125	60	L	6K				
<b>10041P w/wo 1-10</b>	3	125	DC	-	6K	90	1/1	-/-	-
	1	250	DC	-	6K				
	6	125	60	GP	6K				
<b>10041P w/wo 50-99</b>	6	125	60	GP	6K	90	1/1	-/-	-
	1	250	60	GP	6K				
	3	125	60	L	6K				
<b>1035,1036 w/wo 1-10</b>	12	125	DC	-	6K	-	1/1	-/-	-
	6	250	DC	-	6K				
	15	125	60	R	6K				
<b>1045,1046 w/wo 1-10</b>	10	250	DC	-	6K	-	2/1	-/-	-
<b>1419 w/wo 2,K,I, IK,W,WK (200 watt)</b>									
	-	120	60	GP	10K	-	1/3	-/-	-
<b>1440,1441</b>	5	250	DC	-	6K	-	1/M	-/-	-
	10	125	DC	T	6K				
<b>15000 w/wo 1-899</b>	6	120	60	GP	6K	105	2/1	-/-	-
	3	240	60	GP	6K				
<b>15001,15100 w/wo 1-899</b>	6	120	60	GP	6K	105	2/1	-/-	-
	3	240	60	GP	6K				
	3	120	60	L	6K				
	-	120	60	1/10hp	6K				
<b>15005 w/wo 1-899</b>	3	240	60	GP	6K	105	1/M	-/-	-
	6	120	60	L	6K				
	10	120	60	R	6K				

	3	120	60	L	6K				
	-	120	60	1/10hp	6K				
<b>15005 w/wo 1-899</b>	3	240	60	GP	6K	105	1/M	-/-	-
	6	120	60	L	6K				
	10	120	60	R	6K				
	-	120	60	1/10hp	6K				
<b>15101 w/wo 1-899</b>	6	120	60	GP	6K	105	2/1	-/-	-
	3	240	60	GP	6K				
	3	120	60	L	6K				
	-	120	60	1/10hp	6K				
<b>1513,1514 /fb/ followed by 1-50</b>									
	4	125	60	GP	6K	-	1/M	-/-	-
<b>1515,1516 /fb/ followed by 1-100</b>									
	5	125	60	GP	6K	-	1/1	-/-	-
<b>1526 /fb/ followed by 201</b>	5	125	60	GP	6K	-	1/1	-/-	-
<b>1526 w/wo 1-200</b>	3	250	60	GP	6K	-	1/1	-/-	-
	6	125	60	L	6K				
<b>157 /fb/ followed by 0-9 f/b 1,2,3 w/wo 0-9 w/suff</b>									
	15	125	60	GP	6K	65	1/M	-/-	2
	10	250	60	GP	6K				
	-	120-240	60	3/4hp	6K				
<b>1572 w/wo 1-500</b>	3	125	60	GP	6K	90	1/1	-/-	-
	1	250	60	GP	6K				
	1.2	125	60	L	6K				
<b>1577T w/wo 1-200</b>	3	125	DC	-	6K	-	1/1	-/-	-
	1	250	DC	-	6K				
	1.2	125	DC	T	6K				
<b>1585,2585 w/wo 1-100</b>	3	125	DC	-	6K	-	1/2CKT	PP/-	-
	1	250	DC	-	6K				
<b>159 /fb/ followed by 0-9 f/b 1,4 w/wo 0-9 w/suff</b>									
	6	125	60	GP	6K	65	1/M	-/-	2
	3	250	60	GP	6K				
	-	120-240	60	1/4hp	6K				
<b>1684,1685,1686, 1687,1688,1690, 1691 w/wo 1-199</b>									
	8	125	60	GP	6K	105	1/M	-/-	6(18)
	4	250	60	GP	6K				
	-	125-250	60	1/3hp	6K				
<b>1689 w/wo 1-199</b>	3	125	60	L	6K	105	1/M	-/-	6(18)

	6	125	60	GP	6K				
	3	250	60	GP	6K				
	-	125-250	60	1/4hp	6K				
<b>1695 w/wo 1-100 and 3695 w/wo AAA-ZZZ</b>									
	8	125	60	GP	6K	105	1/1	-/-	-
<b>1696 w/wo 1-100 and 3696 w/wo AAA-ZZZ</b>									
	10	125	60	GP	6K	105	1/1	-/-	-
	5	250	60	GP	6K				
<b>1720 w/wo 1-500</b>	6	125	DC	-	6K	65	1/1	-/-	-
	3	250	DC	-	6K				
	3	125	-	T	6K				
<b>1738 w/wo 1-200</b>	8	125	DC	-	6K	65	1/1	-/-	-
<b>1748 w/wo 1-200</b>	10	125	DC	-	6K	65	1/1	-/-	-
<b>1762,1763 w/wo suffixes</b>	20	120	60	GP	10K	-	1/M	-/-	Note 11, 12
<b>1764,1765 w/wo suffixes</b>	20	120-277	60	GP	6K	-	1/M	-/-	Note 11, 12
<b>2570 w/wo 1-200</b>	6	125	DC	-	6K	65	1/1	-/-	-
	3	250	DC	-	6K				
<b>2574L,2575L w/wo 1-999</b>	1	250	60	GP	6K	-	1/1	-/-	-
	3	125	60	L	6K				
<b>2592 w/wo 1-200</b>	3	125	60	GP	6K	105	1/1	-/-	-
	1.5	277	60	GP	6K				
<b>2679 w/wo 1-200</b>	1	250	DC	-	6K	65	1/1	-/-	-
	3	125	DC	T	6K				
<b>3585 w/wo 1-50 w/wo AAA-ZZZ</b>									
	3	125	60	GP	6K	-	1/3 POS	-/-	-
	1	250	60	GP	6K				
<b>3587 w/wo suff</b>	1.5	250	60	GP	6K	-	1/2	-/-	-
	3	125	60	L	6K				
<b>3679,4679 w/wo 1-100 w/wo AAA-ZZZ</b>									
	1	250	60	GP	6K	65	1/1	-/-	-
	3	125	60	L	6K				
<b>3702,3705 w/wo 1-899</b>	3	240	60	GP	6K	105	1/M	-/-	-
	6	120	60	L	6K				
	-	120-240	60	1/4hp	6K				
<b>5410 fb/ followed by 8 w/wo suffix -000 to -999 and one, two or three letters -A to -Z to Cat. No.</b>									
	8	120	60	T	30K	130	1/1	-/-	Note 8, 9
<b>565,566 w/wo 1-25 565 /fb/ followed by 100-110</b>									
	1	125	60	GP	6K	-	1/2	-/-	-
	0.25	250	DC	-	6K				
	0.75	125	DC	T	6K				

<b>57 /fb/ followed by 01,04,21, 24,31,34 f/b 1-20,75-100</b>									
	15	125	60	GP	6K	-	1/2	-/-	-
	10	250	60	GP	6K				
	-	120-240	60	3/4hp	6K				
<b>57 /fb/ followed by 11,13,14, 41,43,44,51,54, f/b 1-20,75-100</b>									
	15	125	60	GP	6K	-	M/2	-/-	-
	10	250	60	GP	6K				
	-	120-240	60	3/4hp	6K				
<b>57 /fb/ followed by 55,56,75, 76,85,86,95,96 f/b 500-700</b>									
	15	125	60	GP	6K	-	1/1	-/-	-
	10	250	60	GP	6K				
	-	120-240	60	3/4hp	6K				
<b>57 /fb/ followed by 55,75,85, 95 /fb/ followed by 1-200</b>									
	6	125	DC	-	6K	-	1/1	-/-	-
	3	250	DC	-	6K				
	-	120-240	60	1/4hp	6K				
<b>57 /fb/ followed by 55,75,85,95 f/b L /fb/ followed by 1-200</b>									
	3	250	60	GP	6K	-	1/1	-/-	-
	6	125	60	L	6K				
<b>57 /fb/ followed by 74,84,94 f/b 1-200</b>									
	6	125	DC	-	6K	-	1/2	-/-	-
	3	250	DC	-	6K				
<b>57 fb/ followed by 57,77,78, 79,87,88,89,97, 98,99 w/wo 1-50, 100-200</b>									
	6	125	DC	-	6K	-	2/M	-/-	-
	3	250	DC	-	6K				
<b>5703</b>	10	250	60	GP	6K	-	1/2	-/-	-
	15	125	60	GP	6K				
	-	240	60	3/4hp	6K				
<b>5703,5723,5733 f/b 1-20,75-100</b>									
	15	125	60	GP	6K	-	1/2	-/-	-
	10	250	60	GP	6K				
	-	240	60	3/4hp	6K				
<b>5715,5725,5735 f/b 1-20,75-100</b>									
	15	125	60	GP	6K	-	1/2	-/-	-
	10	250	60	GP	6K				
	-	120-240	60	1/2hp	6K				
<b>575 w/wo 700-799</b>	1	250	DC	-	6K	65	1/1	-/-	-
	3	125	DC	T	6K				

	15	125	60	GP	6K	-	M/2	-/-	-
	10	250	60	GP	6K				
<b>5766 w/wo 1-50, 100-200</b>	6	125	60	GP	6K	-	1/3 CKT	PP/-	-
	3	250	60	GP	6K				
<b>5767</b>	10	250	60	GP	6K	-	1/2 CKT	PP/-	-
<b>5770 w/wo 1-50</b>	10	125	60	GP	6K	-	1/2 CKT	PP/-	-
	15	250	60	GP	6K				
	5	125	60	L	6K				
<b>5771 w/wo 1-50</b>	15	125	60	GP	6K	-	1/2CKT	PP/-	-
	10	250	60	GP	6K				
	-	120- 240	60	1/2hp	6K				
<b>5772100 w/wo 1-200</b>	5	250	60	GP	6K	-	2/1	-/-	-
	10	125	60	L	6K				
<b>5780 /fb/ followed by 1-20, 75-100</b>									
	6	125	60	GP	6K	-	1/2	-/-	-
	3	250	60	GP	6K				
	-	120- 240	60	1/4hp	6K				
<b>581</b>	1	250	60	GP	6K	-	1/3	-/-	-
	3	125	60	GP	6K				
<b>581 w/wo 1-50 582 w/wo 1-199</b>									
	3	125	DC	-	6K	-	1/2 CKT	-/-	-
	1	250	DC	-	6K				
	3	125	DC	-	6K				
<b>584 w/wo 1-100</b>	3	125	DC	-	6K	-	1/M	PP/-	-
	1	250	DC	-	6K				
	4	125	60	GP	6K				
<b>585 w/wo 1-50</b>	3	125	DC	-	6K	-	1/2 CKT	-/-	-
	1	250	DC	-	6K				
	3	125	60	L	6K				
<b>588</b>	3	125	60	GP	6K	-	1/M	PP/-	-
<b>591 w/wo 1-20, 2591 w/wo 1-200 3591, 4591, 4592 w/wo AAA-ZZZ 1865</b>									
	3	125	60	GP	6K	105	1/1	-/-	Note 6
<b>592 w/wo 1-20</b>	3	125	DC	-	6K	-	1/1	-/-	-
	1	250	DC	-	6K				
<b>6204 w/wo 1,4,5 (200 watt)</b>									
	-	120	60	GP	10K	75	1/1	-/-	Note 2, 3

<b>6250 /fb/ followed by 6-10 and 6201 (200 watt)</b>									
	-	120	60	GP	10K	75	-	-/-	Note 2, 3, 4, 5
<b>6300, 6301 (200 watt)</b>									
	-	120	60	GP	10K	75	-	-/-	Note 2, 3, 4, 5
<b>6304 w/wo 1,4,5 (300 watt)</b>									
	-	120	60	GP	10K	75	1/1	-/-	Note 2, 3
<b>6404 w/wo 1-7 (400 watt)</b>									
	-	120	60	GP	10K	75	1/1	-/-	Note 2, 3
<b>6504 w/wo 1-7 (500 watt)</b>									
	-	120	60	GP	10K	75	1/1	-/-	Note 2, 3
<b>6604 w/wo 1-7 (600 watt)</b>									
	-	120	60	GP	10K	75	1/1	-/-	Note 2, 3
<b>6681 /fb/ followed by 12 (600 watt)</b>									
	-	120	60	GP	10K	-	1/1	-/-	-
<b>679 fb/ followed by 700-799 w/wo 1-200 w/wo AAA-ZZZ</b>									
	1	250	DC	-	6K	90	1/1	-/-	-
	3	125	DC	T	6K				
<b>683 /fb/ followed by 7</b>									
	3	250	DC	-	6K	-	1/4POS	-/-	-
	7	125	DC	T	6K				
<b>689 /fb/ followed by 11-20</b>									
	3	250	DC	-	6K	-	1/2CKT	-/-	-
	7	125	DC	T	6K				
<b>695, w/wo 1-100 and w/wo AAA-ZZZ</b>									
	8	125	60	GP	6K	-	1/1	-/-	-
<b>696 w/wo 1-100 and 3696 w/wo AAA-ZZZ</b>									
	10	125	60	GP	6K	-	1/1	-/-	-
	5	250	60	GP	6K				
<b>701-703 w/wo 1-10</b>									
	6	125	DC	-	6K	-	M/2	-/-	-
	3	250	DC	-	6K				
<b>704 w/wo 1-10</b>									
	6	125	60	GP	6K	-	2/2	-/-	-
	3	250	60	GP	6K				
<b>711 w/wo 1-20</b>									
	6	125	DC	-	6K	-	1/1	-/-	-
	3	250	DC	-	6K				
<b>712 w/wo 1-20</b>									
	6	125	DC	-	6K	-	2/1	-/-	-
	3	250	DC	-	6K				
<b>714 w/wo 1-100, 301-400</b>									
	10	250	60	GP	6K	-	1/1	-/-	-
	20	125	60	GP	6K				
	-	125-250	60	GP	6K				
<b>719 w/wo 1-50</b>									
	3	125	60	GP	6K	-	1/1	-/-	-
	-	125	60	1/10hp	6K				
<b>720,720T w/wo 1-999</b>									
	6	125	60	GP	6K	-	1/1	-/-	-
	3	250	60	GP	6K				

	3	125	60	L	6K				
<b>721 w/wo 1-100</b>	3	125	DC	-	6K	-	1/2CKT	-/-	-
	1	250	DC	-	6K				
<b>723 w/wo 1-100</b>	4	125	DC	-	6K	-	1/2	-/-	-
	1	250	DC	-	6K				
<b>724 w/wo 1-50 714 /fb/ followed by 101-300</b>									
	15	125	60	GP	6K	-	1/1	-/-	-
	10	250	60	GP	6K				
<b>725 w/wo 1-100</b>	6	125	DC	-	6K	-	1/1	-/-	-
	3	250	DC	-	6K				
<b>730 w/wo 1-100</b>	6	125	DC	-	6K	-	1/1	-/-	-
	3	250	DC	-	6K				
<b>735 w/wo 1-100</b>	6	125	DC	-	6K	-	1/1	-/-	-
	3	250	DC	-	6K				
<b>738 w/wo 1-200</b>	8	125	DC	-	6K	-	1/1	-/-	-
<b>8 /fb fb/ followed by 00-06,08,13, 15-17,19,42,56, 57,60 and 3700,3701,3717, 15003 all w/wo 1-899</b>									
	3	240	60	GP	6K	105	1/M	-/-	-
	6	120	60	L	6K				
	10	120	60	R	6K				
	-	120-240	60	1/4hp	6K				
<b>8 fb/ followed by 09,10,12, 14,18,20,23,63 w/wo 1-899</b>									
	10	120	60	GP	6K	105	1/M	-/-	-
	5	240	60	GP	6K				
	-	120	60	1/10hp	6K				
<b>811,15002 w/wo 1-899</b>	10	120	60	GP	6K	105	1/M	-/-	-
	5	240	60	GP	6K				
	-	120	60	1/10hp	6K				
	14	120	60	GP	6K				
<b>824 w/wo 1-899</b>	12	120	60	R	6K	105	1/3	-/-	-
	6	240	60	R	6K				
	-	120-240	60	1/4hp	6K				
<b>831 w/wo 1-25</b>	10	125	60	R	6K	-	2/3	PP/-	-
	5	250	60	R	6K				
<b>838 w/wo 1-899</b>	4	120-277	60	GP	6K	105	1/2	-/-	-
<b>844 w/wo 1-899</b>	3	240	60	GP	6K	105	1/4	-/-	-
	6	120	60	L	6K				
	10	120	60	R	6K				
	5	12	DC	-	6K				
	-	120-240	60	1/4hp	6K				
<b>875-700</b>	3	250	60	GP	6K	105	1/M	-/-	-

	6	125	60	GP	6K				
<b>90,91,92, /fb/ followed by 679 w/wo 1-99</b>									
	1.5	250	60	GP	6K	105	1/1	-/-	-
	3	125	60	L	6K				
<b>90572, 90577 w/wo 1-99</b>	6	125	60	GP	6K	65	1/1	PP/-	Note 10
	3	250	60	GP	6K				
<b>90572L, 90577L w/wo 1-99</b>	3	125	60	GP	6K	65	1/1	PP/-	Note 10
	1	250	60	GP	6K				
	1.5	125	60	L	6K				
<b>92572 /fb/ followed by 1-99</b>									
	6	125	60	GP	6K	75	1/1	-/-	Note 10
	3	250	60	GP	6K				
<b>92572L /fb/ followed by 1-99</b>									
	3	125	60	GP	6K	75	1/1	-/-	Note 10
	1	250	60	GP	6K				
	1.5	125	60	L	6K				
<b>936</b>	1	250	60	GP	6K	105	1/1	-/-	-
	5	12	DC	-	6K				
	3	125	60	T	6K				
<b>937, 938</b>	1	250	60	GP	6K	-	1/1	-/-	-
	3	250	60	GP	6K				
	1	125	60	T	6K				
	5	12	DC	-	6K				
<b>937, 938 w/wo 500</b>	3	125	DC	-	6K	-	1/1	-/-	-
	1	250	DC	-	6K				
	1	125	DC	T	6K				
	5	12	DC	-	6K				
<b>9575,9577 1-249,-500,-749</b>	1	250	60	GP	6K	65	1/1	-/-	-
	3	125	60	L	6K				
<b>9575-250-499, -750-799</b>	1.5	250	60	GP	6K	65	1/1	-/-	Note 10
	3	125	60	L	6K				

Note 1 - The pull chain may be pulled only straight out when operated at any angle other than straight out. The bell nut provided with each switch must be used.

Note 10 - The push in terminals have been evaluated for use only with the illustrated connector.

Note 11 - This switch has been evaluated to the Requirements of UL 20 for the General Purpose Rating.

Note 12 - This switch has been evaluated to the Requirements of UL 508 for the Ballast Rating.

Note 2 - The electric lighting fixture or portable electric lamp utilizing this device should be an incandescent lamp type only.

Note 3 - The fixture or portable electric lamp should be permanently marked 120 V, AC, Maximum Total Lamp Wattage followed by the wattage rating of the switch, in letters not less than 1/16 in high which shall be visible during relamping.

Note 4 - A suitable enclosure shall be provided at least 1-1/4 in diameter or equivalent on 6181, 6201 and 6301 and 3 in diam for 6250-6 to 10 incl. and 6300.


Note 5 - The acceptability of the mounting of Cat. No. 6250-6 to 10 incl. by means of spring metal push on lock nuts or equivalent should be determined.

Note 6 - The suitability of the outlet box of Cat. No. 1865 to function as an overall enclosure has not been investigated.



Note 8 - The switch has been investigated for use with SP-1, SP-2, SPT-1 and SPT-2 cords only.

Note 9 - The switch should be wired with cord having flame resistant properties, identified by the designation FR-1 (VW-1).

Marking: Company name or tradename "E7458" , catalog, model or part number, electrical ratings and the Recognized Component Mark,  on the product or on the smallest unit container in which the product is packaged.

[Last Updated](#) on 2017-05-31

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".