

NZMT2.E15331 - INSULATING BUSHINGS - COMPONENT

Insulating Bushings - Component

See General Information for Insulating Bushings - Component

HEYCO PRODUCTS INC

1800 INDUSTRIAL WAY N
TOMS RIVER, NJ 08755 USA

E15331

Feed-Through Bushings, Model(s) LTBP 1000-063, LTBP 1000-250, LTBP 1093-063, LTBP 1093-250, LTBP 1375-250, LTBP 1500-250, LTBP 500-063, LTBP 500-250, LTBP 625-063, LTBP 625-250, LTBP 750-063, LTBP 750-250, LTBP 875-063, LTBP 875-250, TRG 1000-890, TRG 1093-1000, TRG 1250-1125, TRG 1375-1250, TRG 1500-1375, TRG 2000-1875, TRG 375-270, TRG 500-395, TRG 625-520, TRG 750-645, TRG 875-770, TSB NPT 1/2, TSB NPT 1/4, TSB NPT 3/4, TSB NPT 3/8

Insulating Bushings, Model(s) B 218-125N, B 307-244, B 390-265, B 512-375, B 625-500N, B 687-562, B 750-625N, B 875-750N, B-187-125, B-281-156, B-281-218, B-312-250, B-343-218, B-375-250, B-406-281, B-437-312, B-468-343, B-500-375, B-531-406, B-625-500, B-750-625, B-781-625, B-875-750, B1000-875, B1093-969, B250-187N, B281-218N, B312-250N, B343-218N, B375-250N, B500-375N, K-375-125, K-437-187, K-500-250, K-625-375, K-750-500, K-875-625, MSB 13-10, MSB 16-12, MSB 20-16, MSB 22-18, MSB 25-19, MSB 28-24, MSB 32-26, MSB 34-26, N-500, N-875, OCB-1000, OCB-1093, OCB-1250, OCB-1375, OCB-1500, OCB-2.5, OCB-2000, OCB-375, OCB-437, OCB-500, OCB-512, OCB-562, OCB-625, OCB-650, OCB-750, OCB-866, OCB-875, OCB-984, OCUB-1000, OCUB-1093, OCUB-1250, OCUB-1375, OCUB-1500, OCUB-2.5, OCUB-2000, OCUB-500, OCUB-625, OCUB-750, OCUB-875, S 1000-9, S 1093-10, S 625-4, S 750-5, S 875-9, S-50, S-87, SB-1.00-12, SB-1.093-13, SB-1.093-14, SB-1.093-15, SB-1.187-15, SB-1.187.15, SB-1.250-15, SB-1.50-18, SB-1.500-17, SB-1.500-21, SB-1.750-22, SB-1000-12, SB-1000-SQ500, SB-1093-13, SB-1093-14, SB-1093-15, SB-1093-FFI, SB-1187-15, SB-1250-15, SB-1250-16, SB-1375-14, SB-1375-16, SB-1375-MH100-3, SB-1500-17, SB-1500-18, SB-1500-21, SB-1750-10X570, SB-1750-22, SB-2.00-26, SB-2.093-29, SB-2.25-29, SB-2.5-31, SB-2000-26, SB-2000-28, SB-250-040, SB-250-2, SB-3.0-39, SB-3.375-45, SB-3.5-47, SB-312-3, SB-375-281, SB-375-3, SB-375-4, SB-4.0-55, SB-437-243, SB-437-4, SB-437-5, SB-5.0-70, SB-500-4, SB-500-5, SB-500-6, SB-562-5, SB-562-6, SB-562-7, SB-562-VF-219375, SB-6.0-86, SB-625-4, SB-625-500, SB-625-7, SB-625-8, SB-687-8, SB-687-9, SB-750-10, SB-750-6, SB-750-625, SB-750-8, SB-750-9, SB-812-10, SB-812-9, SB-875-10, SB-875-11, SB-875-6, SB-875-7, SB-875-8, SB-875-9, SB-875-TG375, SB1.375-16, SBHT 500-6, SBT-1.00-12, SBT-1.000-12, SBT-1.093-15, SBT-1.187-15, SBT-1.250-16, SBT-1.375-16, SBT-1.500-12, SBT-1.500-21, SBT-1.750-22, SBT-1093-15, SBT-1187-15, SBT-1250-16, SBT-1375-16, SBT-1500-21, SBT-2.00-26, SBT-2000-26, SBT-500-6, SBT-875-11, SOCB 07M, SOCB 13M, SOCB 16M, SOCB 19M, SOCB 22M, SOCB 24M, SOCB 27M, UB-1000 may begin with prefix S, UB-1093 may begin with prefix S, UB-1187 may begin with prefix S, UB-1250 may begin with prefix S, UB-1375 may begin with prefix S, UB-1500 may begin with prefix S, UB-1750 may begin with prefix S, UB-2.5 may begin with prefix S, UB-2000 may begin with prefix S, UB-3.0 may begin with prefix S, UB-500 may begin with prefix S, UB-625 may begin with prefix S, UB-750 may begin with prefix S, UB-812 may begin with prefix S, UB-875 may begin with prefix S, UBT-1.000 may begin with prefix S, UBT-1.500 may begin with prefix S, UBT-1000 may begin with prefix S, UBT-1093 may begin with prefix S, UBT-1375 may begin with prefix S, UBT-1500 may begin with prefix S, UBT-500 may begin with prefix S, UBT-625 may begin with prefix S, UBT-750 may begin with prefix S, UBT-875 may begin with prefix S

Insulating Bushings Incorporating a Strain Relief, Model(s) ISR300, ISR330, LSR1939-300, RDD-100, RDD-100-7, RDD-100-90, RDD-100A, RDD-100A-7, RDD-100A-90, RDD-101, RDD-101-7, RDD-101-90, RDD-101A, RDD-101A-90, RDD-200, RDD-200-2, RDD-200-2-90, RDD-200-90, RDD-201, RDD-201-2, RDD-201-2-90, RDD-201-90, RDD-301, RDD-301-2, RDD-301-2-90, RDD-301-90, RDD-401, RDD-501, RDD-510, RDD-601, RDD-6N2, RDD-701, ST-100L, ST-100N, ST-100W, ST-101A, ST-101AT, ST-101N, ST-200N, ST-201N, ST-301N, ST301N V0, USR-3, USR-4, USR-40

Insulating Bushings Incorporating a Strain Relief, "straight-thru" cord exit, Model(s) RSR-1109, RSR-875, SR 6N5-4 may be with or without prefix SR, SR 8R-200, SR-2L-1 may be with or without prefix SR, SR-2M-1 may be with or without prefix SR, SR-2M-4 may be with or without prefix SR, SR-2P-1 may be with or without prefix "SR", SR-2P-4 may be with or without prefix SR, SR-30-1 may be with or without prefix SR, SR-300-1 may be with or without prefix SR, SR-302-1 may be with or without prefix SR, SR-31-2 may be with or without prefix "SR", SR-33-1 may be with or without prefix SR, SR-34-1 may be with or without prefix SR, SR-34-2 may be with or without prefix SR, SR-3A-4 may be with or without prefix SR, SR-3L-1 may be with or without prefix SR, SR-3P-1 may be with or without prefix SR, SR-3P-4 may be with or without prefix SR, SR-3W-1 may be with or without prefix SR, SR-4A-6 may be with or without prefix SR, SR-4E-4 may be with or without prefix SR, SR-4K-1 may be with or without prefix SR, SR-4K-4 may be with or without prefix SR, SR-4K-6 may be with or without prefix SR, SR-4L-1 may be with or without prefix SR, SR-4L-4 may be with or without prefix SR, SR-4N-4 may be with or without prefix SR, SR-4N-6 may be with or without prefix SR, SR-4P may be with or without prefix SR, SR-4P-4 may be with or without prefix SR, SR-5K-1 may be with or without prefix SR, SR-5K-4 may be with or without prefix SR, SR-5KN-4 may be with or without prefix SR, SR-5L-1 may be with or without prefix SR, SR-5M-3 may be with or without prefix SR, SR-5MN-3 may be with or without prefix SR, SR-5N-4 may be with or without prefix SR, SR-5P may be with or without prefix SR, SR-5P-1 may be with or without prefix SR, SR-5P-4 may be with or

without prefix SR, SR-5P3-4 may be with or without prefix SR, SR-5W-1 may be with or without prefix SR, SR-6K-5 may be with or without prefix SR, SR-6L may be with or without prefix SR, SR-6L-1 may be with or without prefix SR, SR-6N-4 may be with or without prefix SR, SR-6N2-4 may be with or without prefix SR, SR-6N3-4 may be with or without prefix SR, SR-6N4-4 may be with or without prefix SR, SR-6P-1 may be with or without prefix SR, SR-6P-3 may be with or without prefix SR, SR-6P-4 may be with or without prefix SR, SR-6P10-CEE may be with or without prefix SR, SR-6P3-4 may be with or without prefix SR, SR-6P30-CEE may be with or without prefix SR, SR-6P4-4 may be with or without prefix SR, SR-6P5-4 may be with or without prefix SR, SR-6W-1 may be with or without prefix SR, SR-7K-2 may be with or without prefix SR, SR-7L may be with or without prefix SR, SR-7L-2 may be with or without prefix SR, SR-7N-2 may be with or without prefix SR, SR-7P may be with or without prefix SR, SR-7P-2 may be with or without prefix SR, SR-7W-2 may be with or without prefix SR, SR-8L-1 may be with or without prefix SR, SR-8N-1 may be with or without prefix SR, SR-8N-2 may be with or without prefix SR, SR-8P may be with or without prefix SR, SR-8P-1 may be with or without prefix SR, SR-8P-2 may be with or without prefix SR, SR-8R-2 may be with or without prefix SR, SR-9P-1 may be with or without prefix SR, SR-9P-2 may be with or without prefix SR, SR4N-7 may be with or without prefix SR

Insulating Bushings Incorporating a Strain Relief, 90 degree angle cord exits, Model(s) SR-10-2 may be with or without prefix SR, SR-10N-2 may be with or without prefix SR, SR-11-2 may be with or without prefix SR, SR-11K may be with or without prefix SR, SR-11K-2 may be with or without prefix SR, SR-11L may be with or without prefix SR, SR-13-1 may be with or without prefix SR, SR-14 may be with or without prefix SR, SR-14-1 may be with or without prefix SR, SR-15-1 may be with or without prefix SR, SR-16-1 may be with or without prefix SR, SR-17-2 may be with or without prefix SR, SR-18 may be with or without prefix SR, SR-18-2 may be with or without prefix SR, SR-20-1 may be with or without prefix SR, SR-20L-1 may be with or without prefix SR, SR-21-2 may be with or without prefix SR, SR-21N-2 may be with or without prefix SR, SR-23-1 may be with or without prefix SR, SR-24-1 may be with or without prefix SR, SR14A-1 may be with or without prefix SR

Insulating Bushings Incorporating a Strain Relief, bell shaped cord exits, Model(s) SR-2P-5 may be with or without prefix SR, SR-3P-5 may be with or without prefix SR, SR-4N-5 may be with or without prefix SR, SR-5N-5 may be with or without prefix SR, SR-6N3-5 numbers may be with or without prefix SR, SR-6P-5 may be with or without prefix SR, SR-6P2-5 may be with or without prefix SR, SR-6P3-5 may be with or without prefix SR

Insulating Bushings Incorporating a Strain Relief, employing an integrally molded, flexing spring guard where the cord exits the bushing, Model(s) SR-5N-7 may be with or without prefix SR, SR-5P-7 may be with or without prefix SR, SR-5S-1 may be with or without prefix SR, SR-6N-7 may be with or without prefix SR, SR-6N3-7 may be with or without prefix SR, SR-6P-7 may be with or without prefix SR, SR-6P3-7 may be with or without prefix SR, SR-6S-1 may be with or without prefix SR, SR-6S-2 may be with or without prefix SR, SR-7P-7 may be with or without prefix SR

Strain Relief Bushing, Model(s) ISR-14-27

Marking: Company name or tradename "Heyco" and model designation.

Last Updated on 2018-04-11

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"