



# IMPROVED CERTIFICATIONS SEARCH TOOL. REGISTER NOW!

[LEARN MORE](#)

## OKCT.E5833

### Lampholders, Electric Discharge, 1000 Volts or Less

[Page Bottom](#)

### Lampholders, Electric Discharge, 1000 Volts or Less

[See General Information for Lampholders, Electric Discharge, 1000 Volts or Less](#)

**LEVITON MFG CO INC**

E5833

201 N SERVICE RD  
MELVILLE, NY 11747-3138 USA

Trademark and/or Tradename: "E5833" , "Zipline"

**Circuit interrupting types**, Model(s) 13080\*, 13080-1 to 13080-200\*, 13080W-1 to 13080W-200\*, 13081\*, 13081-1 to 13080-200\*, 13081W-1 to 13081W-200\*, 1997, 1997-1 to 1997-10, 1997W, 1997W-1 to 1997W-10, 1998, 1998-1 to 1998-10, 1998W, 1998W-1 to 1998W-10, 294, 294-1 to 294-10, 294W-1 to 294W-10, 389, 389-1 to 389-100\*, 389-1W to 389-100W\*, 389W, 389W-1 to 389W-100\*, 394, 394-1 to 394-100, 394W, 394W-1 to 394W-100, 437, 437-1 to 437-50

**Combination lampholders with starter holders**, Model(s) 1072, 1072-1 to 1072-20, 1073, 1073-1 to 1073-20, 1076, 1076-1 to 1076-20, 1077, 1077-1 to 1077-20, 12895, 1395, 1395-1 to 1395-10, 1395W, 1395W-1 to 1395W-10, 291, 291W, 381, 381-1 to 381-5, 381W, 381W-1 to 381W-5, 391, 391-1\*, 391-2\*, 391-4\*, 391-6 to 391-50\*, 391N, 391N-1\*, 391N-2\*, 391N-4\*, 391N-6 to 391N-50\*, 391W, 391W-1\*, 391W-2\*, 391W-4\*, 391W-6 to 391W-50\*, 391WN, 391WN-1\*, 391WN-2\*, 391WN-4\*, 391WN-6 to 391WN-50\*, 398, 398-1 to 398-50, 398W, 398W-1 to 398W-50, 399, F-105, F-107

**Electric discharge lampholders, 1000 V or less, HT rated 130 C when marked**, Model(s) 13280\*, 13453\*, 23280\*, 23453

**Electric discharge lampholders, 1000 V or less, lampholder array**, Model(s) 3620C-xx2 (b), 3620C-xx3 (b), 3620C-xx4 (b), 3620R-xx2 (b), 3620R-xx3 (b), 3620R-xx4 (b), 362RC-xx2 (b), 362RC-xx3 (b)

**For circular lamps**, Model(s) 400, 400-1 to 400-10, 402, 402-1 to 402-10, 406, 408, 408-1 to 408-99, 409, 409-1 to 409-10

**For circular lamps, 660 w, 600 v**, Model(s) 407, 407-1 to 407-20

**For semicircular lamps**, Model(s) 387, 387-1 to 387-10

**For use with low pressure sodium lamps, for use in outdoor enclosed signs**, Model(s) 8806, 8806-1 to 8806-500

**For use with Type G23 base lamps, HT rated 120 C when marked**, Model(s) 26719-1 to 26719-500

**For use with type G24q base lamps**, Model(s) 23453 (d), 23454 (d), 23455 (d)

**For use with type G24q base lamps, HT rated 130 C when marked**, Model(s) 13452 (d), 13453 (d), 13454 (d), 13455 (d)

**For use with type G24q base lamps, HT rated 120 C when marked**, Model(s) 26725-201, 26725-202, 26725-203, 26725-211, 26725-212, 26725-213, 26725-221, 26725-223, 26725-2A1, 26725-2A2, 26725-2A3, 26725-401, 26725-402, 26725-403, 26725-411, 26725-412, 26725-413, 26725-414, 26725-415, 26725-419, 26725-421, 26725-422, 26725-423, 26725-424, 26725-429, 26725-4A1, 26725-4A2, 26725-4A4, 26725-4A9

**For use with type G24q base lamps, HT rated 140 C when marked**, Model(s) 26800-4A1, 26800-4A2, 26800-4A8, 26800-4A9

**For use with Type GX23 base lamps, HT rated 120 C when marked**, Model(s) 26720-1 to 26720-500

**Junction boxes mounted, for use with Type GU24 base lamps**, Model(s) 26730, may have suffixes to denote mounting brackets.

**Junction boxes mounted, for use with Type GU24 base lamps**, Model(s) 26735

**Junction boxes mounted, for use with Type GU24 base lamps**, Model(s) 26740, may have suffixes to denote mounting brackets.

**Junction boxes mounted, for use with Type GU24 base lamps**, Model(s) 9850, 9852, 9860, 9862, 9863, Craftmade K212-CF, Craftmade K212PC-CF, Grainger 5MRL1, Grainger 5MRL2

**Miniature bipins**, Model(s) 420, 420-1 to 420-100, 420-21W-1 to 420-21W-100, 420W, 420W-1 to 420W-100

**Miniature bipins, HT rated 130 C when marked**, Model(s) 13654-EXL, 13654-EXS, 13654-SNP, 13654-SWP, 13654-TNP, 13654-TWP, 13666-EXL, 13666-EXS, 13666-SNP, 13666-SWP, 13666-TNP, 13666-TWP, 23654-EXL, 23654-EXS, 23654-SNP, 23654-SWP, 23654-TNP, 23654-TWP, 23666-EXL, 23666-EXS, 23666-SNP, 23666-SWP, 23666-TNP, 23666-TWP, 23670-EXL, 23670-EXS, 23670-SNP, 23670-SWP, 23670-TNP, 23670-TWP, 23671-EXL, 23671-EXS, 23671-SNP, 23671-SWP, 23671-TNP, 23671-TWP

**Recessed double contacts**, Model(s) 1086, 1086-1 to 1086-10, 1087, 1087-1 to 1087-10, 1088, 1088-1 to 1088-10, 1089, 1089-1 to 1089-10, 1092, 1092-1 to 1092-10, 1096, 1096-1 to 1096-50, 1105, 1105-1 to 1105-50, 1105-1P to 1105-50P, 1105-1S to 1105-50S, 1105P, 1105S, 1106, 1106-1 to 1106-50, 1106-1P to 1106-50P, 1106-1S to 1106-50S, 1106P, 1106S, 11103, 11103-1 to 11103-50, 11103-1P to 11103-50P, 11103-1S to 11103-50S, 11103P, 11103S, 11104, 11104-1 to 11104-50, 11104-1P to 11104-50P, 11104-1S to 11104-50S, 11104P, 11104S, 11122, 11122-1 to 11122-50, 11122-1P to 11122-50P, 11122-1S to 11122-50S, 11122P, 11122S, 11124, 11124-1 to 11124-50, 11124-1P to 11124-50P, 11124-1S to 11124-50S, 11124P, 11124S, 1120, 1120-1 to 1120-50, 1120-1P to 1120-50P, 1120-1S to 1120-50S, 1120P, 1120S, 1121, 1121-1 to 1121-50, 1121-1P to 1121-50P, 1121-1S to 1121-50S, 1121P, 1121S, 1123, 1123-1 to 1123-50, 1123-1P to 1123-50P, 1123-1S to 1123-50S, 1123P, 1123S, 13550-ONW\*, 13550-ONW-W\*, 13551-ONW\*, 13551-ONW-W\*, 13570, 13570-ONW, 13571, 13571-ONW, 13572, 13573, 433\*, 443\*, 456-1 to

456-20, 457-1 to 457-20, 492\*, 493\*, 523\*, 523W\*, 524\*, 524W\*, 536, 537

**Recessed double contacts, for use in outdoor enclosed signs**, Model(s) 13464\*, 13465\*, 13550\*, 13550-W\*, 13551\*, 13551-W\*, 13552\*, 13552-W\*, 13553\*, 13553-W\*, 13554\*, 13554-1 to 13554-10\*, 13555\*, 13555-1 to 13555-10\*, 13556\*, 13556-1 to 13556-10\*, 13557\*, 13557-1 to 13557-10\*, 13558\*, 13558-1 to 13558-10\*, 13559\*, 13559-1 to 13559-10\*, 13560\*, 13560-1 to 13560-10\*, 13561\*, 13561-1 to 13561-10\*, 1410-1 to 1410-13, 448, 449, 488, 489, 492, 493

**Recessed double contacts, shunted**, Model(s) 23550-ONW\*, 23550-ONW-W\*, 23551-ONW\*, 23551-ONW-W\*, 23570-ONW, 23571-ONW

**Standard bipins**, Model(s) 1070, 1070-1 to 1070-20, 1071, 1071-1 to 1071-20, 1074, 1074-1 to 1074-20, 1075, 1075-1 to 1075-20, 1078, 1078-1 to 1078-20, 1079, 1079-1 to 1079-20, 1080, 1080-1 to 1080-20, 1081, 1081-1 to 1081-20, 1084, 1084-1 to 1084-20, 1085, 1085-1 to 1085-20, 12894\*, 13080-1W to 13080-200W, 13080W, 13150\*, 13150-1 to 13150-9\*, 13150N\*, 13150NX\*, 13150R\*, 13150U\*, 13151\*, 13151-1 to 13151-9\*, 13151-L\*, 13151-L-1 to 13151-L-9\*, 13151-LN\*, 13151-LNX\*, 13151-LR\*, 13151-LU\*, 13151N\*, 13151NX\*, 13151R\*, 13151U\*, 13152\*, 13152-1 to 13152-9\*, 13152N\*, 13152NX\*, 13152R\*, 13152U\*, 13153\*, 13153-1 to 13153-9\*, 13153-L\*, 13153-L-1 to 13153-L-9\*, 13153-LN\*, 13153-LNX\*, 13153-LR\*, 13153-LU\*, 13153N\*, 13153NX\*, 13153R\*, 13153U\*, 13180\*, 13180-1 to 13180-9\*, 13180N\*, 13180NX\*, 13180R\*, 13180U\*, 13181\*, 13181-1 to 13181-9\*, 13181N\*, 13181NX\*, 13181R\*, 13181U\*, 13250\*, 13250-1 to 13250-9\*, 13250N\*, 13250NX\*, 13250R\*, 13250U\*, 13251\*, 13251-1 to 13251-9\*, 13251N\*, 13251NX\*, 13251R\*, 13251U\*, 13350 - 13359 (a), 13451\*, 13451-18\*, 13451-N\*, 13451-NX\*, 13518\*, 13518W\*, 13519\*, 13519W\*, 13570, 13571, 13572, 13573, 13651NP\*, 13651WP\*, 13652-WWP\*, 13652NP\*, 13652WP\*, 13653NP\*, 13653WP\*, 13660OSL\*, 13660SNP\*, 13660SWP\*, 13661OSL\*, 13661SNP\*, 13661SWP\*, 1377\*, 1377-1 to 1377-100\*, 1377W\*, 1377W-1 to 1377W-100\*, 1390, 1390-100, 1390N, 1390W, 1390W-100, 1390WN, 1394, 1394-1 to 1394-100, 1394-W, 1394W-1 to 1394W-100, 183451-18, 1980, 1980-1 to 1980-10, 1981, 1981-1 to 1981-10, 1982, 1982-1 to 1982-10, 1982N, 1982N-1 to 1982N-10, 1982W, 1982W-1 to 1982W-10, 1982WN, 1982WN-1 to 1982WN-10, 1984, 1984-1 to 1984-10, 1984N, 1984N-1 to 1984N-10, 1985, 1985-1 to 1985-10, 1985N, 1985N-1 to 1985N-10, 1986, 1986-1 to 1986-10, 1986N, 1986N-1 to 1986N-10, 1987, 1987-1 to 1987-10, 1987N, 1987N-1 to 1987N-10, 1990, 1990N, 1990W, 1990WN, 1993, 1993-1 to 1993-10, 1993W, 1993W-1 to 1993W-10, 1995, 1995-1 to 1995-10, 1995N, 1995W, 1995W-1 to 1995W-10, 1995WN, 1995WN-1 to 1995EN-10, 1996, 1996-1 to 1996-10, 1996N, 1996N-1 to 1996N-10, 1996W, 1996W-1 to 1996W-10, 1996WN, 1996WN-1 to 1996WN-10, 23150\*, 23150-1 to 23150-9\*, 23150N\*, 23150NX\*, 23150R\*, 23150U\*, 23151 (a), 23152 (a), 23153 (a), 23350 to 23359 (a), 23350-REJ to 23353-REJ\*, 23451\*, 23518\*, 23518W\*, 23519\*, 23519W\*, 23651NP\*, 23651WP\*, 23652-WWP\*, 23652NP\*, 23652WP\*, 23653NP\*, 23653WP\*, 23660OSL\*, 23660SNP\*, 23660SWP\*, 23661OSL\*, 23661SNP\*, 23661SWP\*, 290, 290-1 to 290-10, 290W, 290W-1 to 290W-10, 377-1 to 377-50, 377-100 to 377-200, 377-600 to 377-700, 377-78, 377W, 377W/1 to 377W/50, 378-1 to 378-10, 378W, 378W-1 to 378W-10, 378W-20, 379, 379-1 to 379-5, 379W, 379W-1 to 379W-5, 390\*, 390/I-390/50\*, 390N\*, 390N/I-390N/50\*, 390N/I-390N/50\*, 390W\*, 390W/I-390W/50\*, 390WN\*, 390WN/I-390WN/50\*, 392, 395\*, 395/1-395/100\*, 395W\*, 395W/1-395W/100\*, 397\*, 397-1 to 397-200\*, 397W\*, 397W-1 to 397W-200\*, 431\*, 431-1 to 431-20\*, 431W\*, 431W-1 to 431W-20\*, 434\*, 434-1 to 434-50\*, 434W\*, 434W-1 to 434W-50\*, 435, 435-1 to 435-50, 436, 436-1 to 436-50, 458, 459, 479, 486\*, 486-1 to 486-199, 486-999, 487\*, 487-1 to 487-199, 487-999, 497, 497-1 to 497-50, 498, 498-1 to 498-100, 498W, 498W-1 to 498W-100, 521\*, 521-1 to 521-50\*, 522\*, 522-1 to 522-50, 522-1 to 522-50\*, 631, 631-1 to 631-100, 631W, 631W-1 to 631W-100, 9378, 9378-1 to 9378-10, 990, 990W, F-103, F-113, F-117

**Standard bipins, HT rated 130 C when marked**, Model(s) 13662OSL\*, 13662SNP\*, 13662SWP\*, 23662OSL\*, 23662SNP\*, 23662SWP\*

**Standard single-pins**, Model(s) 2536, 2537

**Standard single-pins**, Model(s) 1050 (c), 1050-1 to 1050-100 (c), 1051 (c), 1051-1 to 1051-100 (c), 1052 (c), 1052-1 to 1052-100 (c), 1054-1 to 1054-100 (c), 1055 (c), 1055-1 to 1055-100 (c), 1056 (c), 1056-1 to 1056-100 (c), 1060 (c), 1060-1 to 1060-100 (c), 1061 (c), 1061-1 to 1061-100 (c), 450 (c), 451 (c), 452 (c), 452-1 (c), 453 (c), 453-1 (c), 454 (c), 460 (c), 461 (c), 462 (c), 463 (c), 466, 466-3, 467, 467-3, 470 (c), 471 (c), 516 (c), 516\*, 517 (c), 517\*

**Standard single-pins, for use in outdoor enclosed signs**, Model(s) 452-2, 452-3, 453-2, 453-3, 468 (c), 469 (c)

(a) - May be followed by suffix Letters -U, -N, -NX, -D or UNX and/or suffix numbers -1 to -9, may be marked with an I in a circle to indicate instant start.

(b) - Where the 2, 3 or 4 indicates number of lampholders, XX may be alphanumeric used for commercial purposes, may be marked with an I to indicate instant start.

(c) - To be used in parts, Cat. Nos. 1058, 1058-1 to -100, with Cat. Nos. 1059, 1059-1 to -100, Cat. Nos. 1064, 1064-1 to -100, with Cat. Nos. 1065, 1065-1 to -100, 1094, 1094-1 to -100, 1095, 1095-1 to -100, 1097, 1097-1 to -100, 1098, 1098-1 to -100, 1099, 1099-1 to -100, 1100, 1100-1 to -100, 11101, 11101-1 to -100, 11102, 11102-1 to -100.

(d) - May be followed by suffix letters A to Z, and/or suffix numbers -1 to -99.

\* - May be marked with an I in a circle to indicate instant start.

NOTE - This listing includes any of the catalog numbers with added prefix numbers 800-809 and/or added suffixes N, NX, U, W and/or -1 to -9; Catalog numbers can be displayed in the following format: YYY - ABCDE ? XXX, where: YYY denotes optional three-digit prefixes consist of alpha-numeric characters; ABCDE denotes the listed/recognized catalog numbers, where the listed/recognized catalog numbers are less than five digits, preceding 0s (zeros) can be optionally added to make up the five digits; XX or XXX denotes optional two or three-digit suffixes consisting of alpha-numeric characters, where the listed/recognized catalog numbers already contain suffixes that are less than three digits, alphanumeric character(s) can be optionally added to make up the three digits.

[Last Updated](#) on 2017-12-09

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2018 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2018 UL LLC".



# IMPROVED CERTIFICATIONS SEARCH TOOL. REGISTER NOW!

[LEARN MORE](#)**OKCT2.E5833****Lampholders, Electric Discharge, 1000 Volts or Less - Component**[Page Bottom](#)**Lampholders, Electric Discharge, 1000 Volts or Less - Component**[See General Information for Lampholders, Electric Discharge, 1000 Volts or Less - Component](#)**LEVITON MFG CO INC**

E5833

201 N SERVICE RD  
MELVILLE, NY 11747-3138 USA

Cat. Nos. 377-100 to -200 incl. May be marked with an "I" in a circle to indicate Instant Start.

Cat. Nos. 408-100 to -150 incl.

Cat. Nos. 428, 428W also with suffixes -1 to -50 incl.

Catalog numbers can be displayed in the following format: YYY - ABCDE - XXX.

Where: "YYY" denotes optional 3-digit prefixes consist of alpha-numeric characters;

"ABCDE" denotes the listed/recognized catalog numbers, where the listed/recognized catalog numbers are less than 5 digits, preceding "0"s (zeros) can be optionally added to make up the 5 digits;

"XXX" denotes optional 3-digit suffixes consist of alpha-numeric characters, where the listed/recognized catalog numbers already contain suffixes that are less than 3 digits, alpha-numeric character(s) can be optionally added to make up the 3 digits.

Marking: Company name or "E5833" or tradenames "Zipline", "Leviton", "Fluorescent Wiring Devices", "FWD", catalog designation on device or carton.

[Last Updated](#) on 2012-02-09[Questions?](#)[Print this page](#)[Terms of Use](#)[Page Top](#)

© 2018 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2018 UL LLC".



# IMPROVED CERTIFICATIONS SEARCH TOOL. REGISTER NOW!

[LEARN MORE](#)

**OKCT7.E5833**

**Lampholders, Electric Discharge, 1000 Volts or Less Certified for Canada**

[Page Bottom](#)

**Lampholders, Electric Discharge, 1000 Volts or Less Certified for Canada**

[See General Information for Lampholders, Electric Discharge, 1000 Volts or Less Certified for Canada](#)

**LEVITON MFG CO INC**

E5833

201 N SERVICE RD  
MELVILLE, NY 11747-3138 USA

**Electric discharge lampholders, 1000 V or less, HT rated 130 C when marked, Model(s) 13280\*, 23280\***

**Electric discharge lampholders, 1000 V or less, lampholder array, Model(s) 3620C-xx2 (b), 3620C-xx3 (b), 3620C-xx4 (b), 3620R-xx2 (b), 3620R-xx3 (b), 3620R-xx4 (b), 362RC-xx2 (b), 362RC-xx3 (b)**

**For use with type G24q base lamps, HT rated 140 C when marked, Model(s) 26800-4A1, 26800-4A2, 26800-4A8, 26800-4A9**

**Junction boxes mounted, for use with Type GU24 base lamps, Model(s) 26730, may have suffixes to denote mounting brackets.**

**Junction boxes mounted, for use with Type GU24 base lamps, Model(s) 26735**

**Junction boxes mounted, for use with Type GU24 base lamps, Model(s) 26740, may have suffixes to denote mounting brackets.**

**Junction boxes mounted, for use with Type GU24 base lamps, Model(s) 9850, 9852, 9860, 9862, 9863, Craftmade K212-CF, Craftmade K212PC-CF, Grainger 5MRL1, Grainger 5MRL2**

**Miniature bipins, HT rated 130 C when marked, Model(s) 13654-EXL, 13654-EXS, 13654-SNP, 13654-SWP, 13654-TNP, 13654-TWP, 13666-EXL, 13666-EXS, 13666-SNP, 13666-SWP, 13666-TNP, 13666-TWP, 23654-EXL, 23654-EXS, 23654-SNP, 23654-SWP, 23654-TNP, 23654-TWP, 23666-EXL, 23666-EXS, 23666-SNP, 23666-SWP, 23666-TNP, 23666-TWP, 23670-EXL, 23670-EXS, 23670-SNP, 23670-SWP, 23670-TNP, 23670-TWP, 23671-EXL, 23671-EXS, 23671-SNP, 23671-SWP, 23671-TNP, 23671-TWP**

**Recessed double contacts, Model(s) 13550-ONW\*, 13550-ONW-W\*, 13551-ONW\*, 13551-ONW-W\*, 13570, 13570-ONW, 13571, 13571-ONW, 13572, 13573**

**Recessed double contacts, for use in outdoor enclosed signs, Model(s) 13550\*, 13550-W\*, 13551\*, 13551-W\*, 13552\*, 13552-W\*, 13553\*, 13553-W\***

**Recessed double contacts, shunted, Model(s) 23550-ONW\*, 23550-ONW-W\*, 23551-ONW\*, 23551-ONW-W\*, 23570-ONW, 23571-ONW**

**Standard bipins, Model(s) 13660OSL\*, 13660SNP\*, 13660SWP\*, 13661OSL\*, 13661SNP\*, 13661SWP\*, 23660OSL\*, 23660SNP\*, 23660SWP\*, 23661OSL\*, 23661SNP\*, 23661SWP\***

**Standard bipins, HT rated 130 C when marked, Model(s) 13662OSL\*, 13662SNP\*, 13662SWP\*, 23662OSL\*, 23662SNP\*, 23662SWP\***

(b) - Where the 2, 3 or 4 indicates number of lampholders, XX may be alphanumeric used for commercial purposes, may be marked with an I to indicate instant start.

\* - May be marked with an I in a circle to indicate instant start.

NOTE - This listing includes any of the catalog numbers with added prefix numbers 800-809 and/or added suffixes N, NX, U, W and/or -1 to -9; Catalog numbers can be displayed in the following format: YYY - ABCDE ? XXX, where: YYY denotes optional three-digit prefixes consist of alpha-numeric characters; ABCDE denotes the listed/recognized catalog numbers, where the listed/recognized catalog numbers are less than five digits, preceding 0s (zeros) can be optionally added to make up the five digits; XX or XXX denotes optional two or three-digit suffixes consisting of alpha-numeric characters, where the listed/recognized catalog numbers already contain suffixes that are less than three digits, alphanumeric character(s) can be optionally added to make up the three digits.

Trademark and/or Tradename: "E5833" , "Zipline"

[Last Updated](#) on 2017-12-09

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2018 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2018 UL LLC".

