



**GRAND BRASS LAMP PARTS**

[www.GrandBrass.com](http://www.GrandBrass.com)

51 Railroad Avenue  
West Haven, CT 06516

Voice (212) 226-2567 ~ Fax (212) 226-5673

**SINCE ..... 1913**



## Installation Instructions for Pendant Cord Style Fixtures

This Fixture should only be connected to a grounded electrical box supplied by a 120 - 250 volt branch circuit with a 20 amp max. circuit breaker or fuse. Turn the Breaker to the Off Position or Remove the Fuse before installation.

All connections and installation procedures should be in accordance with the National Electric Code and All Local Government Ordinances and Building Codes. If you are Unsure about the installation seek the advice of a Qualified Professional.

1. Remove fixture from box and identify all parts are present.
2. Thread screws through crossbar and mount crossbar as shown in figure.
3. Adjust cord length as shown in figure. Trim cord length as needed.
4. Strip outer insulation exposing inner insulated wire set.
5. Strip just the ends of the inner wires to expose enough bare copper leads to make a connection using properly sized wire nuts.
6. Attach wires as shown in figure.
7. Place canopy over screws in crossbar and secure with cap head nuts.
8. Turn Circuit Breaker on or Reinstall Fuse and Test for Proper Operation.

Re-lamp with 60 Watt Max E-26 Edison Type Bulbs or Equivalent.

White Wire = Neutral  
 Black Wire = Hot  
 Green Wire = Ground

