

**OKCT.E5833****Lampholders, Electric Discharge, 1000 Volts or Less**[Page Bottom](#)**Lampholders, Electric Discharge, 1000 Volts or Less**[See General Information for Lampholders, Electric Discharge, 1000 Volts or Less](#)**LEVITON MFG CO INC**201 N SERVICE RD
MELVILLE, NY 11747-3138 USA

E5833

Trademark and/or Tradename: "E5833", "Zipline"

Electric discharge lampholders, 1000 v or less, Cat. Nos. 13280, 23280, 13453, 23453; Models 13280, 23280 may be marked with an "I" in a circle, to indicate Instant Start and are "HT" rated 130 C, when so marked.

Electric discharge lampholders, 1000 V or less - Lampholder Array, Cat. Nos. 3620C-xx2, 3620C-xx3, 3620C-xx4, 3620R-xx2, 3620R-xx3, 3620R-xx4, 362RC-xx2, 362Rc-xx3. Where the 2, 3 or 4 indicates number of lampholders and the XX may be alphanumeric used for commercial purposes. Models may be marked with an "I" to indicate Instant Start.

Miniature bipin, Cat. Nos. 420, 420-1 to 420-100 incl., 420-21W-1 to 420-21W-100 incl., 420W, 420W-1 to 420W-100 incl.

Cat. Nos. 13654, 23654, 13666, 23666, 23670 and 23671 with suffixes -EXL, -EXS, -SWP, -SNP, -TWP or -TNP. "T" rated 130 C when so marked.

Standard bipin, Cat. Nos. F-103, F-113, F-117, 290, 290-1 to 290-10 incl., 290W, 290W-1 to 290W-10 incl., 377-78, 377-1 to 377-50 incl., 377-600 to 377-700 incl., 377W, 377W/1 to -/50 incl., 378-1 to -10 incl., 378W, 378W-1 to -10 incl., 378W-20, 379, 379-1 to -5 incl., 379W, 379W-1 to -5 incl., 390, 390/1 to -/50 incl., 390N, 390N/1 to -/50 incl., 390W, 390W/1 to -/50 incl., 390WN, 390WN/1 to -/50 incl., 392, 395, 395/1 to -/100 incl., 395W, 395W/1 to -/100 incl., 397, 397W, 397-1 to -200 incl., 397W-1 to -200 incl., 431, 431-1 to -20 incl., 431W, 431W-1 to -20 incl., 434, 434-1 to -50 incl., 434W, 434W-1 to -50 incl., 435, 435-1 to -50 incl., 436, 436-1 to -50 incl., 458, 459, 479, 486-1 to -199 incl., 486-999, 487-1 to -199 incl., 487-999, 497, 497-1 to -50 incl., 498, 498-1 to -100 incl., 498W, 498W-1 to -100 incl., 521, 521-1 to -50 incl., 522, 522-1 to -50 incl., 631, 631-1 to -100 incl., 631W, 631W-1 to -100 incl., 990, 990W, 1070, 1070-1 to -20 incl., 1071, 1071-1 to -20 incl., 1074, 1074-1 to -20 incl., 1075, 1075-1 to -20 incl., 1078, 1078-1 to -20 incl., 1079, 1079-1 to -20 incl., 1080, 1080-1 to -20 incl., 1081, 1081-1 to -20 incl., 1084, 1084-1 to -20 incl., 1085, 1085-1 to -20 incl., 13518, 13519 with or without suffix W; Cat. Nos. 1377, 1377-1 to -100 incl., 1377W, 1377W-1 to -100 incl., 1390, 1390-100, 1390N, 1390W, 1390W-100, 1390WN, 1394, 1394-1 to -100 incl., 1394-W, 1394W-1 to -100 incl., 1980, 1980-1 to -10 incl., 1981, 1981-1 to -10 incl., 1982, 1982-1 to -10 incl., 1982N, 1982N-1 to -10 incl., 1982W, 1982W-1 to -10 incl., 1982WN, 1982WN-1 to -10 incl., 1984, 1984-1 to -10 incl., 1984N, 1984N-1 to -10 incl., 1985, 1985-1 to -10 incl., 1985N, 1985N-1 to -10 incl., 1986, 1986-1 to -10 incl., 1986N, 1986N-1 to -10 incl., 1987, 1987-1 to -10 incl., 1987N, 1987N-1 to -10 incl., 1990, 1990N, 1990W, 1990WN, 1993, 1993-1 to -10 incl., 1993W, 1993W-1 to -10 incl., 1995, 1995-1 to -10 incl., 1995N, 1995-1 to -10 incl., 1995W, 1995W-1 to -10 incl., 1995WN, 1995WN-1 to -10 incl., 1996, 1996-1 to -10 incl., 1996N, 1996N-1 to -10 incl., 1996W, 1996W-1 to -10 incl., 1996WN, 1996WN-1 to -10 incl., 9378, 9378-1 to -10 incl., 12894; Cat. Nos. 13080W, 13080-1W to -200W incl., Cat. Nos. 183451-18, 13570-73 incl.; Cat. Nos. 23518, 23519 with or without suffix W.

Cat. Nos. 390, 390N, 390/1-50 incl., 390N/1-50 incl., 390N/1-50 incl., 390W, 390WN, 390W/1-50 incl. 390WN/1-50 incl. 395, 395/1-100 incl., 395W, 395W/1-100 Incl., 397, 397-1 to 200 incl., 397W, 397W-1 to 200 incl., 12894 may be marked with an "I" in a circle to indicate instant start.

Cat. Nos. 431, 431W with or without Suffix Nos. -1 to -20 incl., may be marked with an "I" in a circle to indicate instant start.

Cat. Nos. 13518, 13519, 23518, 23519 with or w/o Suffix W, may be marked with an "I" in a circle to indicate instant start.

Cat. Nos. 486, 487 may be marked with an "I" in a circle to indicate instant start.

Cat. Nos. 521, 521-1 to -50 incl., 522, 522-1 to -50 incl. may be marked with an "I" in a circle to indicate instant start.

Cat. Nos. 1377, 1377-1 to -100 incl., 1377W, 1377W-1 to -100 incl. may be marked with an "I" in a circle to indicate instant start.

Cat. Nos. 434, 434W also with Suffix Numbers -1 to -50 incl., may be marked with an "I" in a circle to indicate instant start.

Cat. No. 377 with Suffixes -100 to -200 incl.

Cat. Nos. 13451, 13451-N, 13451-NX, 13451-18 and 23451. May be marked with an "I" in a circle to indicate Instant Start.

Cat. Nos. 13150, 23150, 13151, 13151-L, 13152, 13153, 13153-L, 13180, 13181, 13250, 13251 also with suffixes N, NX, R, U and -1 to -9 incl. May be marked with an "I" in a circle to indicate Instant Start.

Cat. Nos. 13350 - 13359, 23151 to 23153 incl., 23350 to 23359 incl.; also with suffix Letters -U, -N, -NX, -D or *UNX and/or suffix numbers -1 to -9 incl; Cat. Nos. 23350 to 23353 incl. may be provided with additional suffix letters -REJ. Lampholders may be marked with an "I" in a circle to indicate Instant Start.

Cat. Nos. 13651, 23651, 13652, 23652, 13653, 23653 with suffixes WP or NP, may be marked with an "I" in a circle to indicate Instant Start; Cat. Nos. 13652, 23652 with suffixes -WWP, may be marked with an "I" to indicate Instant Start; Cat. Nos. 13660, 13661, 23660, 23661, 13662, 23662 with suffixes OSL, SWP and SNP, may be marked with an "I" in a circle to indicate Instant Start; Cat. Nos. 13660, 13661, 23660, 23661 with suffixes -OSL, -SWP, -SNP, may be marked with an "I" in a circle to indicate Instant Start; Cat. Nos. 13662, 23662. "HT" rated 130 C when so marked. Models 13662, 23662 may be marked with an "I" to indicate Instant Start, may be marked with an "I" in a circle to indicate Instant Start.

Circuit interrupting type, Cat. Nos. 294, 294-1 to -10 incl., 294W-1 to -10 incl., 389, 389-1 to -100 incl., 389-1W to -100W incl., 389W, 389W-1 to -100 incl., 394, 394-1 to -100 incl., 394W, 394W-1 to -100 incl., 437, 437-1 to -50 incl., 1997, 1997-1 to -10 incl., 1997W, 1997W-1 to -10 incl., 1998, 1998-1 to -10 incl., 1998W, 1998W-1 to -10 incl.

Cat. No. 389 with suffixes -1 to -100 incl. and -1W to -100W incl.; Cat. No. 389W with suffixes -1 to -100 incl. marked with an "I" in a circle indicate Instant Start.

Cat. Nos. 13080, 13081 also with suffix numbers -1 to -200 incl., also with suffix W. May be marked with an "I" in a circle to indicate Instant Start.

Combination lampholders with starter holders, Cat. Nos. F-105, F-107, 291, 291W, 381, 381-1 to -5 incl., 381W, 381W-1 to -5 incl., 391, 391N, 391W, 391WN, 391-1, 391N-1, 391W-1, 391WN-1, 391-2, 391N-2, 391W-2, 391WN-2, 391-4, 391N-4, 391W-4, 391WN-4, 391-6 to -50 incl., 391N-6 to -50 incl., 391W-6 to -50 incl., 391WN-6 to -50 incl., 398, 398-1 to -50 incl., 398W, 398W-1 to -50 incl., 399, 1072, 1072-1 to -20 incl., 1073, 1073-1 to -20 incl., 1076, 1076-1 to -20 incl., 1077, 1077-1 to -20 incl., 1395,

1395-1 to -10 incl., 1395W, 1395W-1 to -10 incl., 12895.

Lampholders, Models 391-1, 391W-1, 391N-1, 391WN-1, 12895.

Models 391-1, 391W- with suffixes -2, -4, -6 to -50 incl. also with suffix N after basic number may be marked with an "I" in a circle to indicate Instant Start.

For semicircular lamps, Cat. Nos. 387, 387-1 to -10 incl.

For circular lamps, Cat. Nos. 400, 400-1 to -10 incl., 402, 402-1 to -10 incl., 407, 407-1 to -20 incl., 660 w, 600 v, Cat. Nos. 406, 408, 408-1 to -99 incl., 409, 409-1 to -10 incl.

Recessed double contact, Cat. Nos. 448*, 449*, 456-1 to -20 incl., 457-1 to -20 incl., 488*, 489*, 492*, 493*, 536, 537, 1086, 1086-1 to -10 incl., 1087, 1087-1 to -10 incl., 1088, 1088-1 to -10 incl., 1089, 1089-1 to -10 incl., 1092, 1092-1 to -10 incl., 1096, 1096-1 to -50 incl.; Cat. Nos. 1105, 1105-1 to -50 incl., 1106, 1106-1 to -50 incl., 1120, 1120-1 to -50 incl., 1121, 1121-1 to -50 incl., 1123, 1123-1 to -50 incl., 11103, 11103-1 to -50 incl., 11104, 11104-1 to -50 incl., 11122, 11122-1 to -50 incl., 11124, 11124-1 to -50 incl., also with suffixes S and/or P; Cat. Nos. 1410* to -13* incl., 13550*, 13550-W*, 13551*, 13551-W*, 13550-ONW, 13551-ONW; shunted versions 23550-ONW, 23551-ONW; 13552*, 13552-W*, 13553*, 13553-W*, 13554*, 13554-1* to -10* incl., 13555*, 13555-1* to -10* incl., 13556*, 13556-1* to -10* incl., 13557*, 13557-1* to -10* incl., 13558*, 13558-1* to -10* incl., 13559*, 13559-1* to -10* incl., 13560*, 13560-1* to -10* incl., 13561*, 13561-1* to -10* incl.

Cat. Nos. 443, 433, 492, 493 may be marked with an "I" in a circle to indicate Instant Start.

Cat. Nos. 13554, 13554-1 to -10 incl., 13555, 13555-1 to -10 incl., 13556, 13556-1 to -10 incl., 13557, 13557-1 to -10 incl., 13558, 13558-1 to -10 incl., 13559, 13559-1 to -10 incl., 13560, 13560-1 to -10 incl., 13561, 13561-1 to -10 incl. number may be marked with an "I" in a circle to indicate Instant Start.

Cat. Nos. 13550, 13550-ONW, 13551, 13551-ONW, 13552, 13553 and shunted versions 23550-ONW, 23551-ONW, all with or without suffix -W may be marked with an "I" in a circle to indicate Instant Start.

Cat. Nos. 13464*, 13465*. Lampholders may be marked with an "I" in a circle to indicate Instant Start.

Cat. Nos. 523, 524 also with suffix letter W. Lampholders may be marked with an "I" in a circle to indicate Instant Start.

Models 13570, 13571, 13572, 13573, 13570-ONW, 13571-ONW; shunted versions 23570-ONW, 23571-ONW.

Standard single-pin, Cat. Nos. 450, 451, 452, 452-1, 453, 453-1, 454, 460, 461, 462, 463, 468*, 469*, 470, 471, 516, 517, 534N, 535N, 1050, 1050-1 to -100 incl., 1051, 1051-1 to -100 incl., 1052, 1052-1 to -100 incl., 1054, 1054-1 to -100 incl., 1055, 1055-1 to -100 incl., 1056, 1056-1 to -100 incl., 1060, 1060-1 to -100 incl., 1061, 1061-1 to -100 incl.; to be used in parts, Cat. Nos. 1058, 1058-1 to -100 incl., with Cat. Nos. 1059, 1059-1 to -100 incl., Cat. Nos. 1064, 1064-1 to -100 incl., with Cat. Nos. 1065, 1065-1 to -100 incl., 1094, 1094-1 to -100 incl., 1095, 1095-1 to -100 incl., 1097, 1097-1 to -100 incl., 1098, 1098-1 to -100 incl., 1099, 1099-1 to -100 incl., 1100, 1100-1 to -100 incl., 11101, 11101-1 to -100 incl., 11102, 11102-1 to -100 incl.

Cat. Nos. 516, 517 may be marked with an "I" in a circle to indicate Instant Start.

Cat. Nos. 466, 466-3, 467, 467-3.

Cat. Nos. 452-2*, 452-3*, 453-2*, 453-3*.

Cat. Nos. 2536, 2537.

For use with low pressure sodium lamps, Cat. Nos. 8806*, 8806-1* to -500* incl.

For use with Type G23 base lamp, Cat. Nos. 26719-1 to 26719-500 incl. "HT" rated 120 C when so marked.

For use with Type GX23 base lamp, Cat. Nos. 26720-1 to 26720-500 incl. "T" rated 120 C when so marked.

For use with Type G24q base lamps, Cat. Nos. 26725-201, 26725-202, 26725-203, 26725-211, 26725-212, 26725-213, 26725-221, 26725-223, 26725-2A1, 26725-2A2, 26725-2A3, 26725-401, 26725-402, 26725-403, 26725-411, 26725-412, 26725-413, 26725-414, 26725-415, 26725-419, 26725-421, 26725-422, 26725-423, 26725-424, 26725-429, 26725-4A1, 26725-4A2, 26725-4A4, 26725-4A9. "HT" rated 120 C when so marked. Cat. Nos. 26800-4A1, 26800-4A2, 26800-4A8, 26800-4A9. "T" rated 140 C when so marked.

Cat. Nos. 13452, 13453, 23453, 13454, 23454, 13455, 23455, also with suffix letters A to Z incl., and/or suffix numbers -1 to -99 incl. "T" rated 130 C when so marked.

Junction box mounted, For use with Type GU24 base lamp, Cat. Nos. 9850, 9852, 9860, 9862, 9863, Craftmade K212-CF, Craftmade K212PC-CF, Grainger 5MRL1, Grainger 5MRL2.

Type GU24 base lamps, Cat. Nos. 26730+, 26735, 26740+.

"+" - indicates may contain suffixes to denote mounting brackets.

* - Also for use in outdoor enclosed signs.

Note: This listing includes any of the above catalog numbers with added prefix numbers 800-809 incl. and/or added suffixes N, NX, U, W and/or -1 to -9 incl.

Catalog numbers can be displayed in the following format: YYY - ABCDE - XXX.

Where: "YYY" denotes optional three-digit prefixes consist of alpha-numeric characters;

"ABCDE" denotes the listed/recognized catalog numbers, where the listed/recognized catalog numbers are less than five digits, preceding "0"s (zeros) can be optionally added to make up the five digits;

"XX" or "XXX" denotes optional two or three-digit suffixes consisting of alpha-numeric characters, where the listed/recognized catalog numbers already contain suffixes that are less than three digits, alpha-numeric character(s) can be optionally added to make up the three digits.

[Last Updated](#) on 2017-02-02

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".



**OKCT2.E5833****Lampholders, Electric Discharge, 1000 Volts or Less - Component**[Page Bottom](#)**Lampholders, Electric Discharge, 1000 Volts or Less - Component**[See General Information for Lampholders, Electric Discharge, 1000 Volts or Less - Component](#)**LEVITON MFG CO INC**

E5833

201 N SERVICE RD
MELVILLE, NY 11747-3138 USA

Cat. Nos. 377-100 to -200 incl. May be marked with an "I" in a circle to indicate Instant Start.

Cat. Nos. 408-100 to -150 incl.

Cat. Nos. 428, 428W also with suffixes -1 to -50 incl.

Catalog numbers can be displayed in the following format: YYY - ABCDE - XXX.

Where: "YYY" denotes optional 3-digit prefixes consist of alpha-numeric characters;

"ABCDE" denotes the listed/recognized catalog numbers, where the listed/recognized catalog numbers are less than 5 digits, preceding "0"s (zeros) can be optionally added to make up the 5 digits;

"XXX" denotes optional 3-digit suffixes consist of alpha-numeric characters, where the listed/recognized catalog numbers already contain suffixes that are less than 3 digits, alpha-numeric character(s) can be optionally added to make up the 3 digits.

Marking: Company name or "E5833" or tradenames "Zipline", "Leviton", "Fluorescent Wiring Devices", "FWD", catalog designation on device or carton.

[Last Updated](#) on 2012-02-09[Questions?](#)[Print this page](#)[Terms of Use](#)[Page Top](#)

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".

**OKCT7.E5833****Lampholders, Electric Discharge, 1000 Volts or Less Certified for Canada**[Page Bottom](#)**Lampholders, Electric Discharge, 1000 Volts or Less Certified for Canada**[See General Information for Lampholders, Electric Discharge, 1000 Volts or Less Certified for Canada](#)**LEVITON MFG CO INC**

E5833

201 N SERVICE RD
MELVILLE, NY 11747-3138 USA

Miniature Bi-Pins, Cat. Nos. 13280, 23280, may be marked with and "I" in a circle to indicate Instant Start. "HT" rated 130 C when so marked.

Cat. Nos. 13654, 23654, 13666, 23666, 23670 and 23671 with suffixes -EXL, -EXS, -SWP, -SNP, -TWP or -TNP. "HT" rated 130 C when so marked.

Electric discharge lampholders, 1000 V or less - Lampholder Array, Cat. Nos. 3620C-xx2, 3620C-xx3, 3620C-xx4, 3620R-xx2, 3620R-xx3, 3620R-xx4, 362RC-xx2, 362Rc-xx3. Where the 2, 3 or 4 indicates number of lampholders and the XX may be alphanumeric used for commercial purposes. Models indicated may be marked with an "I" to indicate Instant Start.

Recessed double contact lampholders, Cat. Nos. 13550, 13551, 13552, 13553, 13550-ONW, 13551-ONW; shunted versions 23550-ONW, 23551-ONW, all with or without suffix -W may be marked with an "I" in a circle to indicate Instant Start.

Medium bi-pin electric discharge lampholders, Cat. Nos. 13570, 13571, 13572, 13573, 13570-ONW, 13571-ONW; shunted versions 23570-ONW, 23571-ONW.

Cat. Nos. 13660, 13661, 13662, 23660, 23661, 23662 with suffixes OSL, SWP or SNP. Cat. Nos. 13662, 23662. "HT" rated 130 C when so marked and may also be marked with an "I" to indicate Instant Start and may be marked with an "I" in a circle to indicate Instant Start.

Junction box mounted, For use with Type GU24 base lamp, Cat. Nos. 9850, 9852, 9860, 9862, 9863, Craftmade K212-CF, Craftmade K212PC-CF, Grainger 5MRL1, Grainger 5MRL2.

Type GU24 base lamps, Cat. Nos. 26730+, 26735, 26740+.

For use with Type G24q base lamps, Cat. Nos. 26800-4A1, 26800-4A2, 26800-4A8, 26800-4A9. "T" rated 140 C when so marked.

"+" - indicates may contain suffixes to denote mounting brackets.

Catalog numbers can be displayed in the following format: YYY - ABCDE - XXX.

Where: "YYY" denotes optional three-digit prefixes consist of alpha-numeric characters;

"ABCDE" denotes the listed/recognized catalog numbers, where the listed/recognized catalog numbers are less than 5 digits, preceding "0"s (zeros) can be optionally added to make up the five digits;

"XX" or "XXX" denotes optional two or three-digit suffixes consisting of alpha-numeric characters, where the listed/recognized catalog numbers already contain suffixes that are less than three digits, alpha-numeric character(s) can be optionally added to make up the three digits.

Trademark and/or Tradename: "Zipline"

[Last Updated](#) on 2017-02-02[Questions?](#)[Print this page](#)[Terms of Use](#)[Page Top](#)

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".