



**UL Product iQ**  
 UL'S NEXT GENERATION CERTIFICATIONS SEARCH  
 The same trusted data in a modern search engine.

**NOW AVAILABLE**

[▶ LEARN MORE](#)

**WHAC.E488137**  
**Switches for Appliances**

[Page Bottom](#)

**Switches for Appliances**

[See General Information for Switches for Appliances](#)

**ARDITI SPA**

E488137

VIA CABERARDI 3  
 24012 VAL BREMBILLA, BG ITALY

Cat. No.	Load	Watts	Volts	Hz	T Rating	Pol/ Thr	Endurance Cycles	IP	Dis Full (mm)/ Micro	Pollution Degree	Ball Pressure (°C)	Glow Wire (°C) (tE ≤ 2 s)	PTI (V)	Appliance Classification	Std
<b>Switch</b>															
1012S LAMP LFP/ 1012AS LAMP LFP	L	4-250	220-240	50/60	35	1/1	1E4	20	electronic	2	75	650	175	I or II	IEC 61058 1:2000+A1+A2 IEC 61058-2 1:2010
	L	4-200	120												
	CFL lamp (max. 4 lamps)	11-25	100-240												
	LED lamp (max. 4 lamps)	4-25	100-240												
1012S ML LFP/ 1012AS ML LFP	LED Modules (max. 4 modules)	4-25	100-240	50/60	35	1/1	1E4	20	electronic	2	75	650	175	I or II	IEC 61058 1:2000+A1+A2 IEC 61058-2 1:2010
1004P LAMP LFP	L	4-150	220-240	50/60	35	—	1E4	20	electronic	2	75	650	175	II	IEC 61058 1:2000+A1+A; IEC 61058-2 1:2010
	L	4-100	120	50/60	35	—	1E4	20	electronic	2	75	650	175	II	IEC 61058 1:2000+A1+A; IEC 61058-2 1:2010
	SpecL (CFL lamp Dimmable max. 4 lamps)	11-25	100-240	50/60	35	—	1E4	20	electronic	2	75	650	175	II	IEC 61058 1:2000+A1+A; IEC 61058-2 1:2010
1004P ML LFP	SpecL (LED lamp Dimmable 2max. 4 - lamps)	4-25	100-240	50/60	35	—	1E4	20	electronic	2	75	650	175	II	IEC 61058 1:2000+A1+A; IEC 61058-2 1:2010
	SpecL (LED modules max. 4 modules)	4-25	100-240	50/60	35	—	1E4	20	electronic	2	75	650	175	II	IEC 61058 1:2000+A1+A; IEC 61058-2 1:2010

[Last Updated](#) on 2018-06-09

[Questions?](#)

[Print this page](#)


[Terms of Use](#)

[Page Top](#)

© 2018 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2018 UL LLC".





# UL Product iQ

UL'S NEXT GENERATION CERTIFICATIONS SEARCH  
The same trusted data in a modern search engine.

NOW AVAILABLE

[LEARN MORE](#)

WHAC7.E488137

Switches for Appliances Certified for Canada

[Page Bottom](#)

Switches for Appliances Certified for Canada

[See General Information for Switches for Appliances Certified for Canada](#)

**ARDITI SPA**

VIA CABERARDI 3  
24012 VAL BREMBILLA, BG ITALY

E488137

Cat. No.	Load	Watts	Volts	Hz	T Rating	Po/ Thr	Endurance Cycles	IP	Dis Full (mm)/ Micro	Pollution Degree	Ball Pressure (°C)	Glow Wire (°C) (tE ≤ 2 s)	PTI (V)	Appliance Classification	Std
<b>Switch</b>															
1012S LAMP LFP/ 1012AS LAMP LFP	L	4-250	220-240	50/60	35	1/1	1E4	20	electronic	2	75	650	175	I or II	CSA C22.2 NO. 61058-1-09
	L	4-200	120												
	CFL lamp (max. 4 x)	11-25	100-240												
	LED lamp (max. 4 x)	4-25	100-240												
1012S ML LFP/ 1012AS ML LFP	LED Modules (max. 4 x)	4-25	100-240	50/60	35	1/1	1E4	20	electronic	2	75	650	175	I or II	CSA C22.2 NO. 61058-1-09
1004P LAMP LFP	L	4-150	220-240	50/60	35	—	1E4	20	electronic	2	75	650	175	II	CSA C22.2 NO. 61058-1-09
	L	4-100	120	50/60	35	—	1E4	20	electronic	2	75	650	175	II	ICSA C22.2 NO. 61058-1-09
	SpecL (CFL lamp Dimmable max. 4 lamps)	11-25	100-240	50/60	35	—	1E4	20	electronic	2	75	650	175	II	CSA C22.2 NO. 61058-1-09
1004P ML LFP	SpecL (LED lamp Dimmable 2max. 4 - lamps)	4-25	100-240	50/60	35	—	1E4	20	electronic	2	75	650	175	II	CSA C22.2 NO. 61058-1-09
	SpecL (LED modules max. 4 modules)	4-25	100-240	50/60	35	—	1E4	20	electronic	2	75	650	175	II	CSA C22.2 NO. 61058-1-09

[Last Updated](#) on 2018-06-09

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2018 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their

entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2018 UL LLC".