

FEED THE CORDS THROUGH THE CANOPY PORTS AND TIGHTEN WITH THE TINY SET SCREWS IN THE PORTS, THEN PUT THE PLASTIC STRAIN RELIEFS ON THE CORDS DIRECTLY ABOVE THE CANOPY (TO KEEP THE CORDS FROM SLIPPING THROUGH THE PORTS). THEN SLIDE OPTIONAL DECEORATIVE CHECK RING AND SHADE ONTO THE THREADED SOCKET CUP AND SECURE USING THREADED SOCKET RING.

\*DO NOT OVER TIGHTEN THREADED SOCKET RING TO AVOID BREAKING THE GLASS SHADE.

THIS ASSEMBLY IS FOR GLASS SHADES WITH A LIP OR NECK.

PLUGS SUPPLIED IN PARTS PACKAGE TO REPLACE THE PORTS)

ITEM #125 – 5 PENDANT ASSEMBLY (USE ALL 5 PORT CONNECTIONS)

ITEM #123 – 3 PENDANT ASSEMBLY (USE ONLY 3 PORT CONNECTIONS)

(WHEN INSTALLING ONLY 3 PENDANTS PLUG THE (2) UNUSED PORTS USING THE BLANK PLUGS SUPPLIED IN PARTS PACKAGE TO REPLACE THE PORTS)

FEED THE CORDS THROUGH THE CANOPY PORTS AND TIGHTEN WITH THE TINY SET SCREWS IN THE PORTS, THEN PUT THE PLASTIC STRAIN RELIEFS ON THE CORDS DIRECTLY ABOVE THE CANOPY (TO KEEP THE CORDS FROM SLIPPING THROUGH THE PORTS). ATTACH THE HR-314B HOLDER ONTO THE THREADED SOCKET CUP USING THREADED SOCKET RING, THEN SLIDE THE SHADE INTO THE HR-314B HOLDER AND THIGHTEN EVENLY USING THE (3) THUMB SCREWS TO HOLD SHADE IN PLACE.

\*DO NOT OVER TIGHTEN (3) THUMB SCREWS TO AVOID BREAKING THE GLASS SHADE.

GLASS SHADES, METAL SHADES & BULBS ARE OPTIONAL

