

Insulating Tape

COMPANY

ACHEM TECHNOLOGY CORP

6F
397 Xingshan Rd Nehu District
Taipei, 11469 Taiwan

E52811

Cat. No.	Color	Flame Retardant ^[1]	Sunlight Resistant ^[2]	Cold Resistant ^[3]
Thermoplastic tapes. For use as sole insulation				
101	All except clear	No	No	No
FR101	All except clear	Yes	Yes	Yes
FR201	All except clear	Yes	Yes	Yes
FR301, K11N0, K11M0	All	Yes	Yes	Yes
FR302	All except Red	Yes	Yes	Yes
FR401, K18A0	All except clear	Yes	Yes	Yes
K11G0	All except clear	Yes	Yes	Yes

Cookies on UL Solutions

We use cookies to personalize content and ads, to provide social media features and to analyze our traffic. We also share information about your use of our site with our social media, advertising and analytics partners. [Learn more](#)

[3] Tape may be used in applications where the tape will be wrapped or installed at temperatures down to minus 10°C when marked with "Cold Resistance".

Trademark and/or Tradename: "ACHEM", "E52811", "wonder",  wonder® **ACHEM**

Last Updated on 2021-08-24

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2023 UL LLC."

Cookies on UL Solutions

We use cookies to personalize content and ads, to provide social media features and to analyze our traffic. We also share information about your use of our site with our social media, advertising and analytics partners. [Learn more](#)

Insulating Tape - Component

COMPANY

ACHEM TECHNOLOGY CORP

6F
397 Xingshan Rd Nehu District
Taipei, 11469 Taiwan

E52811

Cat. No.	Color	Temp (°C)	Flame Retardant+	Optional Ratings	
				Sunlight Resistant+	Cold Resistant+
PET film insulating tapes with acrylic adhesive					
54X0X10X2	All	130	No	No	No
Polyester film insulating tapes with acrylic adhesive					
2404	Clear	105	No	No	No
2405	Clear	105	No	No	No
Polyester film insulating tapes with rubber adhesive					
2402	Yellow	130	No	No	No
2403	Yellow	130	No	No	No
PVC film insulating tapes with rubber adhesive					
201	All	80	Yes	No	No

Cookie 2403 UL Solutions

We use cookies to personalize content and ads, to provide social media features and to analyze our traffic. We also share information about your use of our site with our social media, advertising and analytics partners. Learn more

+ Complies with "Flame Retardant" and/or "Cold Resistant" and/or "Sunlight Resistant" requirements if authorized in the table above and when so marked.

0X2 - Optional suffixes denoting tape color.

X0 - May be followed by 3, 4, 5 or 6, denoting thickness 0.053, 0.060, 0.070 or 0.080 mm, respectively.

X1 - Optional suffixes denoting release liner type

Marking: Company name or tradename "ACHEM", "E52811", "wonder" or trademark  , **wonder[®]** , **ACHEM** , catalog designation printed On the central paper core Or outer package.

Last Updated on 2021-08-24

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2023 UL LLC."

Cookies on UL Solutions

We use cookies to personalize content and ads, to provide social media features and to analyze our traffic. We also share information about your use of our site with our social media, advertising and analytics partners. [Learn more](#)